



Additional Specs

LIDS-166-ZF



LIDS-250-ZR



LIDS-500-ZR



LIDS-BIB-ZF



Outer Diameter	10.13"	14.68"	20.08"	11.17"
Platen Size	9.96"	11.96"	17.00"	14.92"
Height	0.8" / 24mm	0.98" / 24mm	0.98" / 24mm	0.59" / 15mm
Designed for	Slim sixth	Slim quarter	Traditional quarter and half	2.5 gallon and 5.0 gallon BIB
Load bearing	400-pound max	400-pound max	600-pound max	100-pound max
Platen Material	Carbon steel	Carbon steel	Carbon steel	Tempered glass
Perimeter	Zero footprint	Zero rise / easy keg loading	Zero rise / easy keg loading	Zero footprint
Slope Compensation	No	No	No	Yes, multi-axis accelerometer
On/Off Switch	Yes, rocker switch	Yes, rocker switch	Yes, rocker switch	Yes, tactile switch



Additional Specs

All models include:

- ✓ Bluetooth, low-energy technology with 500' line of sight
- ✓ Rechargeable 4000 mAh lithium polymer battery
- ✓ Approximately three year single battery charge
- ✓ USB-C charge port with cover
- ✓ High impact PC-ABS pedestal
- ✓ 0°F to 120°F operating temp
- ✓ Low voltage
- ✓ FCC certified
- ✓ Rated IP67 for high-moisture / wet environments
- ✓ Fixed three-minute measurement cadence
- ✓ Uses <0.5 MB bandwidth per day
- ✓ Temperature monitoring
- ✓ Commercial-grade demand sensor build to last 10+ years